



HD SPRUNG AXLE ORDER FORM - LAND

	NOW OR ORDERED	SALES ORDER #	
	IBT PO NUMBER	INVOICE #	
Company	Salesman Initials	Date Ordered	Time
Name	Technician Initials	Date Needed	
Phone	Customer PO #	Time Needed	
Measured By Iron Bear: Initials _____ AND _____			
OR Customer: Phone _____ Axle Tag #: _____			

Straight Axle



Quantity	Capacity				Type		ROUND TUBE ONLY Tube Diameter	
1 2 3 <input type="checkbox"/>	10KGD:9-123 Drum	9K	10KHD	12K	Beam	Idler	4"	5" <input type="checkbox"/>
	10KGD:9-44 Drum	15K	16K	<input type="checkbox"/>	Brake	<input type="checkbox"/>		
Brakes		Flange	Hubface	Spring Center	Oversize HF 80"		Bolt Pattern	
Hyd-Disc Hyd-Drum		Measurement <input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		865	8 on 275MM <input type="checkbox"/>
NEV'R Adjust Air <input type="checkbox"/>								
Studs/Nuts				Lubrication		Brand		
5/8" Flange 22mm				Grease Oil <input type="checkbox"/>		Dexter LCI <input type="checkbox"/>		
Nut Upgrade 5/8" Swivel OR 5/8" Cone <input type="checkbox"/>								
Spring Pad								
2.5" Adjustable 003-173-03 10KGD		3" Adjustable 003-173-01 10KGD-16K		3" Upgrade 3-66 10KGD-10KHD		3" Standard 3-66 12K-16K		Hutch 3-403 <input type="checkbox"/>
Spring Pads								
Loose	Underslung (Springs Under)			Overslung (Springs Over)			Spring Pads Both <input type="checkbox"/>	
								
Flange Measurements								
10K GD (8-415 or 8-430 Hub, 9-123 Drum) = Outside of flanges + 10.98								
10K GD (8-288 Hub or 9-44 Drum) = Outside of flanges + 13.50								
10K HD Hub Face = Outside of flanges + 14.35								
12K E = Outside of flanges + 15.27								
12K Disc = Outside of flanges + 14.35								

Notes

Ship LTL	Delivery Direction			U-Bolts		QTY 1 2 3		
	North	East	South	UBK-4X2	UBK-4X2.5	UBK-4X3		
	NE	West	Local	UBK-5X2.5	UBK-5X3	UBK-575		

Bold & Italics indicate Upgrades/Additional Charges