



DEXTER MEDIUM DUTY SPRUNG AXLE ORDER FORM - LAND

NOW OR ORDERED			SALES ORDER #		
IBT PO NUMBER			INVOICE #		
Company			Salesman Initials		Date Ordered
Name			Technician Initials		Date Needed
Phone			Customer PO #		Time Needed
Measured By Iron Bear: Initials _____ AND _____ OR Customer: Phone _____ Axe Tag #: _____					

Straight Axle



Quantity			Capacity			Type		ROUND TUBE ONLY		
1	2	3	10KGD:9-123 Drum	9K	10KHD	12K	Beam	Idler	Tube Diameter	
			10KGD:9-44 Drum	15K	16K	<input type="checkbox"/>	Brake	<input type="checkbox"/>	4"	5"
			Brakes	Flange	Hubface	Spring Center	Oversize HF 80"	Bolt Pattern		
			Hyd-Disc	Hyd-Drum	<input type="checkbox"/>	<input type="checkbox"/>		865	8 on 275MM	<input type="checkbox"/>
			NEV'R Adjust	Air <input type="checkbox"/>	Measurement	<input type="checkbox"/>	<input type="checkbox"/>			<input type="checkbox"/>
			Studs/Nuts			Lubrication		Brand		
			5/8" Flange	22mm	<input type="checkbox"/>	Grease	Oil <input type="checkbox"/>	Dexter	LCI	<input type="checkbox"/>
			Nut Upgrade 5/8" Swivel OR 5/8" Cone			<input type="checkbox"/>				
Spring Pads										
2.5" Adjustable 003-173-03 10KGD			3" Adjustable 003-173-01 10KGD-16K			3" Upgrade 3-66 10KGD-10KHD		3" Standard 3-66 12K-16K		Hutch 3-403
Loose			Underslung (Springs Under)			Overslung (Springs Over)		Spring Pads Both		<input type="checkbox"/>
Spring Pads										
Flange Measurements										

10K GD (8-415 or 8-430 Hub, 9-123 Drum) = Outside of flanges + 10.98

10K GD (8-288 Hub or 9-44 Drum) = Outside of flanges + 13.50

10K HD Hub Face = Outside of flanges + 14.35

12K E = Outside of flanges + 15.27

12K Disc = Outside of flanges + 14.35

Notes

Ship LTL	Delivery Direction			U-Bolts			QTY	1	2	3
	North	East	South	UBK-4X2	UBK-4X2.5	UBK-4X3				
	NE	West	Local	UBK-5X2.5	UBK-5X3	UBK-575				