



DEXTER TORSION AXLE ORDER FORM - LAND

SALES ORDER # INVOICE # IBT PO #											
Company						Salesman Initials		Date Ordered		Time	
Name						Technician Initials		Date Needed			
Phone						Customer PO #		Time Needed			
Measured By Iron Bear: Initials _____ AND _____ OR Customer: Phone _____ Axle Tag #: _____											
Quantity 1 2 3		Capacity	Torflex #	Type Beam Idler Brake		Bearings Timken Import		Prewire Yes - Use Part # Prewire No	Cambered Yes No	Flange Yes No Measurement	
Brakes Hyd-Disc Air Manual Hyd-Drum Hyd-Drum FB NEV'R Adjust		Hub Face Oversize HF 96"		OS Bracket	IS Bracket Norco	Bracket Height 1" 3" LoPro		Bracket Type Dexter (Standard) Featherlite AL-KO Norco			
Standard Reverse 		Bolt Pattern - 3.5K & Above 5 on 4.5 5 on 4.75 5 on 5 5 on 5.5		Studs/Nuts 1/2" 9/16" 5/8" Flange Nut Upgrade 5/8" Swivel OR 5/8" Cone		Degree	Bolt Pattern - 2.2K 440 BT8/9-440 545 8-10" Wheel: BT8/9-545SF 545 12-15" Wheel: BT8/9-545LF				
Lubrication E-Z Lube NEV'R Lube Grease (Solid Caps) Oil		Finish Paint (standard) Galvanized	Top Shock Brkt E1492 22.5D Only Bottom Shock Brkt E1493		V-Bend Yes No		Bearing Buddy Marine Grease		Removable Spindle Upgrade Use Part Number REMOVABLE SPINDLES		
Triple Application #12T-EXT #12EXTREME #13T-EXT #13EXTREME		2.2K Spindle Upgrade #84 Upgrade	7K 5/8" Stud Upgrade Use Part No. 12DU	7K 5/8" Oil Upgrade Use Part No. 12DU-Oil	3.5K Idler Upgrade 845475 84555 84655 Use Part Number IU			3.5K Drum Upgrade 845476 84557 84656 Use Part Number 10DU			
Flange Measurements 2.2K Hub Face = Outside of flanges + 6.90 3.5K Hub Face = Outside of flanges + 6.34 4K, 4.4K Hub Face = Outside of flanges + 7.08 5.2K, 6K, 7K Hub Face = Outside of flanges + 8.73 7.2K & 8K Narrow Hub Face = Outside of flanges + 7.54 8K Hub Face = Outside of flanges + 9.09 10K GD (8-415 & 8-430) = Outside of flanges + 10.98 10K GD (8-288) = Outside of flanges + 13.50 10K HD Hub Face = Outside of flanges + 14.35 12K E = Outside of flanges + 15.27 12K Disc = Outside of flanges + 14.35										 Start Angle (measure when unloaded) 22.5° Up 10° Up 0° 10° Down 22.5° Down 32° Down 45° Down	
Torflex #	Tube Size	Capacity	Top Mount (D)	Side Mount (C)	Bracket Width (G)	Brake	Spindle			AL Bracket	Steel Bracket
#9	2.17"	1000-2200	7.75"	8.0"	2.0"	7 x 1.75	BT or 84			AP180	AP165
#10	2.62"	2300-3500	8.0"	8.0"	2.5"	10 x 2.25	84			AP181	AP166
#10L	2.62"	3K	8.0"	8.0"	2.5"	10 x 1.5	84			AP181	AP166
#10F	2.62"	4K	8.0"	8.0"	2.5"	10 x 2.25	84			AP181	AP166
#11F	3.03"	4.4K	9.0"	9.5"	2.5"	10 x 2.25	Straight			AP182	AP167
#11	3.03"	4100-6000	9.0"	9.5"	2.5"	12 x 2	42			AP182	AP167
#12	3.50"	5.5K-7K	9.0"	9.5"	2.5"	12 x 2	42			AP183	AP168
#12V	3.50"	7.2K	9.0"	9.5"	2.5"	12.25 x 2.5	42			AP183	AP168
#12T	3.88"	5.5K-7K	10.56"	10.56"	2.5"	12 x 2	42			N/A	AP169
#13	3.88"	8K	10.56"	10.56"	2.5"	12.25 x 3.38	42			N/A	AP169
#13N	3.88"	8K	10.56"	10.56"	2.5"	12.25 x 2.5	42			N/A	AP169
#13T	3.88"	8K	10.56"	10.56"	2.5"	12.25 x 3.38	42			N/A	AP169
Notes / Special Instructions:					Ship LTL	Delivery Direction North South East NE West Local					

Bold & Italics indicate Upgrades/Additional Charges